Ser. No. 10/718,175 filed 11/19/2003
Kajekar et al – GAU 2453 (Chea)
Reply to Final Office Action with RCE

AMENDMENTS TO THE CLAIMS

1.   (Currently Amended) A method of determining network penetration, the method

comprising the computer-implemented steps of:

receiving first information that identifies a packet;

representing a possible travel of [[a]] the packet in a network based on topology data

and on security policy data;

wherein the step of representing comprises:

checking the first information against an inbound access control list (ACL),

included in the security policy data, of an interface of a network device

comprising a network entry point for the packet, wherein checking the

first information against the inbound ACL includes determining whether

the inbound ACL permits ingress of the packet at the network device;

if the inbound ACL permits the ingress of the packet at the network device,

checking the first information against one or more outbound ACLs for

each outbound interface of the network device to determine one or more

possible outbound interfaces on which egress of the packet is permitted

from the network device;

checking the topology data to determine one or more neighbor network devices

that the packet could reach, wherein the one or more neighbor network

devices are respectively connected to the one or more possible outbound

interfaces on which the egress of the packet is permitted from the

network device;

for each of the one or more possible outbound interfaces on which the egress of

Ser. No. 10/718,175 filed 11/19/2003
Kajekar et al – GAU 2453 (Chea)
Reply to Final Office Action with RCE

~~the packet is permitted,~~ repeating the checking steps ~~with respect to~~ <u>for</u>

each neighbor network device<u>, of the one or more neighbor network</u>

<u>devices,</u> that is connected to each of the one or more possible outbound

interfaces;

providing an output that specifies a possible penetration of the packet into the network,

based on the step of representing<u>, wherein the output comprises second</u>

<u>information that specifies one or more of: possible paths that the packet could</u>

<u>take in the network, and a set of network devices that the packet could reach in</u>

<u>the network</u>;

wherein the steps of the method are performed by one or more computer systems.

2.   (Currently Amended) ~~A method as recited in~~ <u>The method of</u> Claim 1, wherein the

security policy data comprises one or more access control lists of one or more network

devices in the network.

3.   (Currently Amended) ~~A method as recited in~~ <u>The method of</u> Claim 1, ~~further~~

~~comprising the step of receiving~~ <u>wherein the first information comprises</u> packet

parameters.

4.   (Currently Amended) ~~A method as recited in~~ <u>The method of</u> Claim 3, wherein the

packet parameters comprise <u>an identifier of</u> the network entry point where the packet

enters the network.

5.   (Currently Amended) ~~A method as recited in~~ <u>The method of</u> Claim 3, wherein the

Ser. No. 10/718,175 filed 11/19/2003
Kajekar et al – GAU 2453 (Chea)
Reply to Final Office Action with RCE

packet parameters comprise a destination address.

6.   (Currently Amended) ~~A method as recited in~~ The method of Claim 1, wherein the

topology data is received as input related to a user interface.

7.   (Currently Amended) ~~A method as recited in~~ The method of Claim 1, wherein the

security policy data is based on access control lists associated with input received in a

user interface.

8.   (Currently Amended) ~~A method as recited in~~ The method of Claim 1, wherein the step

of representing further compris~~ing~~es determining a maximum penetration point.

9.   (Currently Amended) ~~A method as recited in~~ The method of Claim 1, wherein the step

of representing comprises accessing the security policy data and the topology data

related to a neighbor network device for which it has been determined that the packet

could reach.

10.   (Currently Amended) ~~A method as recited in~~ The method of Claim 1, wherein the step

of representing comprises determining whether ingress is allowed to a neighbor network

device for which it has been determined that ~~the inbound interface~~ could be reached by

the packet.

11.   (Currently Amended) ~~A method as recited in~~ The method of Claim 1, wherein the step

of representing comprises determining whether there are any neighboring network

devices to a neighbor network device for which it has been determined that the packet

Ser. No. 10/718,175 filed 11/19/2003
Kajekar et al – GAU 2453 (Chea)
Reply to Final Office Action with RCE

could reach.

12.   (Currently Amended) ~~A method as recited in~~ The method of Claim 1, wherein the step

of representing comprises determining whether there are any outbound interfaces that

have not yet been checked for whether there is another network device connected

thereto.

13.   (Currently Amended) ~~A method as recited in~~ The method of Claim 12, wherein the step

of representing comprises recursively applying the step of determining whether there

are any outbound interfaces.

14.   (Canceled)

15.   (Currently Amended) ~~A method as recited in c~~ The method of Claim 1, further

comprising receiving <u>third information that specifies</u> packet parameters ~~specifying~~

~~information~~ corresponding to a plurality of <u>different</u> packets.

16.   (Currently Amended) ~~A method as recited in c~~ The method of Claim 1, wherein the step

of representing comprises:

for a neighbor network device for which it is determined that the packet could reach,

determining if a static routing table is present; and

if the static routing table is present, then

accessing the static routing table, and

determining an outbound interface through which egress of the packet <u>from the</u>

<u>neighbor network device</u> is permitted based on the static routing table.

Ser. No. 10/718,175 filed 11/19/2003
Kajekar et al – GAU 2453 (Chea)
Reply to Final Office Action with RCE

17. (Currently Amended) The method of ~~e~~Claim 16, further comprising not considering any outbound interface through which egress of the packet is permitted by the static routing table but is not permitted by an access control list associated with the security policy data.

18. (Currently Amended) ~~A method as recited in c~~ The method of Claim 1, wherein the step of representing comprises:

for a neighbor network device for which it is determined that the packet could reach, determining if a static routing table is present; and

if the static routing table is not present, then for each outbound interface of the neighbor network device, representing an egress by the packet as part of the representing of the possible travel of the packet.

19. (Currently Amended) ~~A method as recited in c~~ The method of Claim 1, wherein the step of receiving the first information further comprises receiving packet parameters that support transmission control protocol flags.

20. (Currently Amended) ~~A method as recited in c~~ The method of Claim 1, wherein the ~~results~~ output comprises a graphical display of at least ~~allowed paths of the packet~~ the second information.

21. (Currently Amended) ~~A method as recited in c~~ The method of Claim 19, wherein the graphical display also includes at least a mapping of the set of network devices and connections between the network devices in the set of network devices.

Ser. No. 10/718,175 filed 11/19/2003
Kajekar et al – GAU 2453 (Chea)
Reply to Final Office Action with RCE

22.   (Currently Amended) A method of determining potential penetration of ~~a~~ packet<u>s</u> into a

network, the method comprising the computer-implemented steps of:

receiving network topology data;

receiving first information defining a packet flow comprising a source address;

receiving second information defining a first network device, comprising a network

address and an ingress interface identifier for an ingress interface <u>of the first</u>

<u>network device</u>;

determining whether the ingress interface of the first network device allows the packet

flow to enter the first network device, based on <u>checking the first information</u>

<u>against</u> a first access control list associated with the ingress interface;

determining one or more egress interfaces of the first network device that allow egress

of the packet flow <u>from the first network device</u>, based on <u>checking the first</u>

<u>information against</u> one or more second access control lists associated with the

one or more egress interfaces;

based on the network topology data, determining one or more second network devices

that are coupled to the one or more egress interfaces; and

recursively performing the determining steps for each of the one or more second

network devices;

wherein the steps of the method are performed by one or more computer systems.

23.   (Currently Amended) ~~A method as recited in~~ <u>The method of</u> Claim 22, further

comprising the step[[s]] of determining if a static routing table is present <u>for the first</u>

<u>network device</u>, and wherein the step of determining the one or more egress interfaces

~~is performed based on~~ <u>further comprises checking the first information against</u> the static

Ser. No. 10/718,175 filed 11/19/2003
Kajekar et al – GAU 2453 (Chea)
Reply to Final Office Action with RCE

routing table.

24.   (Currently Amended) The method of eClaim 23, further comprising not considering an

~~outbound~~ egress interface through which egress of the packet flow is permitted by the

static routing table but is not permitted by the one or more second access control lists.

25.   (Currently Amended) A method of determining network penetration, the method

comprising the computer-implemented steps of:

representing a travel of a packet in a network based on topology data and on security

        policy data including at least the steps of:

        receiving first information that defin~~in~~ge**s** a packet by at least specifying a

                source address for the packet ~~, an entry port, and a destination port~~ and

                an entry point that identifies a current network device in the network;

        starting a loop for [[a]] the current network device;

        accessing access control list**s** (ACL**s**) in the security policy data stored in an

                ACL database and the topology data stored in a topology database;

        deciding whether an ingress interface of [[a]] the current network device allows

                entry of the packet into the current network device by checking the first

                information against an inbound ACL, from the security policy data, that

                is associated with the ingress interface of the current network device,

                wherein:

        if the entry is not permitted, then terminating the loop for the current

                network device[[,]];

        if the entry is permitted, then ~~performing the steps of:~~

Ser. No. 10/718,175 filed 11/19/2003
Kajekar et al – GAU 2453 (Chea)
Reply to Final Office Action with RCE

checking the first information against one or more outbound

ACLs, from the security policy data, for each outbound

interface of the current network device to determine one

or more possible outbound interfaces on which egress of

the packet is permitted from the current network device;

~~continuing the loop;~~

determining if a static routing table is present for the current network device,

wherein:

if the static routing table is present then determining ~~to~~ from which

outbound interface outbound traffic is permitted to exit the

current network device[[,]]; and

if the static routing table is not present, then determining that the

outbound traffic is allowed to exit through all outbound interfaces

of the current network device;

based on the topology data, determining if there are any neighboring network

devices that are connected to the one or more possible outbound

interfaces on which the egress of the packet is permitted from the current

network device, wherein:

if there are not any neighboring network devices, then returning an

indication of the current network device as a maximum

penetration point as at least part of results of the step of

representing, and terminating the loop for the current network

device;

~~if there is at least one neighboring network device, then continuing the~~

Ser. No. 10/718,175 filed 11/19/2003
Kajekar et al – GAU 2453 (Chea)
Reply to Final Office Action with RCE

~~loop;~~

determining whether or not there are any remaining possible outbound interfaces

for which results of a possible egress of the packet have not been

determined, wherein:

if there are no more remaining possible outbound interfaces, then

terminating the loop <u>for the current network device</u>[[,]]<u>;</u>

if there are more remaining <u>possible outbound</u> interfaces, then setting the

current network device to a neighboring network device that

corresponds to one of the remaining possible outbound

interfaces[[,]]<u>;</u> and

if the loop has not been terminated ~~for the current network device~~, then

restarting the loop for the current network device;

wherein the steps of the method are performed by one or more computer systems.

26.   (Currently Amended) An apparatus for determining penetration into a network, the

apparatus comprising:

one or more processors;

a topology database storing topology information about the network;

an Access Control List (ACL) database storing ACL<u>s</u> ~~information~~ related to the

network;

a <u>non-transitory</u> computer-readable storage medium storing one or more sequences of

instructions that comprise instructions for displaying a penetration Graphical

User Interface (GUI) including at least:

input fields having at least:

Ser. No. 10/718,175 filed 11/19/2003
Kajekar et al – GAU 2453 (Chea)
Reply to Final Office Action with RCE

a topology information input field,

an ACL input field,

a source address input field for ~~entering~~ receiving at least a source

address of a packet, and

an entry point field for ~~entering~~ receiving at least one entry point to the

network for the packet~~, and~~

~~a destination input field for entering at least a destination address for the~~

~~packet~~; and

output penetration information fields for a graphical output including:

network devices of the network,

connections between the network devices corresponding to the topology

information ~~data~~,

at least one entry point to the network,

paths the packet is allowed to follow based on the topology ~~data~~

information and the ACLs ~~data~~, and

at least one maximum penetration point; and

a penetration module configured to:

access the topology database to retrieve the topology information;

access the ACL database to retrieve the ACLs;

receive input corresponding to the input fields;

check the source address of the packet, specified in the source address input

field, against an inbound ACL of an interface of a network device

specified ~~by the input~~ in the entry point field;

if the inbound ACL permits ingress of the packet at the network device, check

Ser. No. 10/718,175 filed 11/19/2003
Kajekar et al – GAU 2453 (Chea)
Reply to Final Office Action with RCE

the source address of the packet against one or more outbound ACLs for

each outbound interface of the network device to determine one or more

possible outbound interfaces on which egress of the packet is permitted

from the network device;

check the topology information to determine one or more neighbor network

devices that the packet could reach, wherein the one or more neighbor

network devices are respectively connected to the one or more possible

outbound interfaces on which the egress of the packet is permitted from

the network device;

repeat the checks for each neighbor network device, of the one or more neighbor

network devices, that is connected to each of the one or more possible

outbound interfaces on which the egress of the packet is permitted from

the network device; and

produce ~~the output penetration information~~ the graphical output for display in

the penetration GUI.

27.   (Currently Amended) An apparatus for determining network penetration, the apparatus

comprising:

one or more processors, and a non-transitory computer-readable storage medium storing

one or more sequences of instructions that comprise instructions which, when

executed by the one or more processors, cause the one or more processors to

perform the steps of:

receiving first information that identifies a packet;

representing a possible travel of [[a]] the packet in a network based on topology

Ser. No. 10/718,175 filed 11/19/2003
Kajekar et al – GAU 2453 (Chea)
Reply to Final Office Action with RCE

data and on security policy data;

wherein the step of representing comprises:

checking <u>the first information against</u> an inbound access control list

(ACL), included in the security policy data, of an interface of a

network device comprising a network entry point for the packet<u>,</u>

<u>wherein checking the first information against the inbound ACL</u>

<u>includes determining whether the inbound ACL permits ingress</u>

<u>of the packet at the network device</u>;

if the inbound ACL permits <u>the</u> ingress of the packet <u>at the network</u>

<u>device</u>, checking <u>the first information against</u> one or more

outbound ACLs for each outbound interface of the network

device to determine one or more possible outbound interfaces on

which egress of the packet is permitted <u>from the network device</u>;

<u>checking the topology data to determine one or more neighbor network</u>

<u>devices that the packet could reach, wherein the one or more</u>

<u>neighbor network devices are respectively connected to the one</u>

<u>or more possible outbound interfaces on which the egress of the</u>

<u>packet is permitted from the network device</u>;

~~for each of the one or more possible outbound interfaces on which the~~

~~egress of the packet is permitted,~~ repeating the checking steps

~~with respect to~~ <u>for</u> each neighbor network device<u>, of the one or</u>

<u>more neighbor network devices,</u> that is connected to each of the

one or more possible outbound interfaces;

providing an output that specifies a possible penetration of the packet into the

Ser. No. 10/718,175 filed 11/19/2003
Kajekar et al – GAU 2453 (Chea)
Reply to Final Office Action with RCE

network, based on the step of representing, wherein the output comprises
second information that specifies one or more of: possible paths that the
packet could take in the network, and a set of network devices that the
packet could reach in the network.

28.   (Currently Amended) ~~An apparatus as recited in~~ The apparatus of Claim 27, wherein
the security policy data comprises one or more access control lists stored on one or
more network devices in the network.

29.   (Currently Amended) ~~An apparatus as recited in~~ The apparatus of Claim 27, wherein
~~the one or more sequences of instructions further comprise instructions which, when~~
~~executed by the one or more processors, cause the one or more processors to perform~~
~~the step of receiving~~ the first information comprises packet parameters.

30.   (Currently Amended) ~~An apparatus as recited in~~ The apparatus of Claim 29, wherein
the packet parameters comprise an identifier of the network entry point where the
packet enters the network.

31.   (Currently Amended) ~~An apparatus as recited in~~ The apparatus of Claim 29, wherein
the packet parameters comprise a destination address.

32.   (Currently Amended) ~~An apparatus as recited in~~ The apparatus of Claim 27, wherein
the topology data is based on input related to a user interface.

33.   (Currently Amended) ~~An apparatus as recited in~~ The apparatus of Claim 27, wherein

Ser. No. 10/718,175 filed 11/19/2003
Kajekar et al – GAU 2453 (Chea)
Reply to Final Office Action with RCE

the security policy data is based on access control lists associated with input related to a user interface.

34. (Currently Amended) ~~An apparatus as recited in~~ The apparatus of Claim 27, wherein the ~~one or more sequences of~~ instructions <u>that cause the one or more processors to perform the step of representing</u> further comprise instructions which, when executed by the one or more processors, cause the one or more processors to perform the step of determining a maximum penetration point.

35. (Currently Amended) ~~An apparatus as recited in~~ The apparatus of Claim 27, wherein the instructions that cause the one or more processors to perform the step of representing comprise instructions which, when executed by the one or more processors, cause the one or more processors to perform the step of accessing the security policy data and the topology data related to a neighbor network device for which it has been determined that the packet could reach.

36. (Currently Amended) ~~An apparatus as recited in~~ The apparatus of Claim 27, wherein the instructions that cause the one or more processors to perform the step of representing comprise instructions which, when executed by the one or more processors, cause the one or more processors to perform the step of determining whether ingress is allowed to a neighbor network device ~~whose inbound interface~~ for which it has been determined that the packet could reach.

37. (Currently Amended) ~~An apparatus as recited in~~ The apparatus of Claim 27, wherein

Ser. No. 10/718,175 filed 11/19/2003
Kajekar et al – GAU 2453 (Chea)
Reply to Final Office Action with RCE

the instructions that cause the one or more processors to perform the step of

representing comprise instructions which, when executed by the one or more

processors, cause the one or more processors to perform the step of determining

whether there are any neighboring network devices to a neighbor network device for

which it has been determined that the packet could reach.

38.   (Currently Amended) ~~An apparatus as recited in~~ The apparatus of Claim 27, wherein

the instructions that cause the one or more processors to perform the step of

representing comprise instructions which, when executed by the one or more

processors, cause the one or more processors to perform the step of determining

whether there are any outbound interfaces that have not yet been checked for whether

there is another network device connected thereto.

39.   (Currently Amended) ~~An apparatus as recited in~~ The apparatus of Claim 38, wherein

the instructions that cause the one or more processors to perform the step of

representing comprise instructions which, when executed by the one or more

processors, cause the one or more processors to perform the step of recursively applying

the step of determining whether there are any outbound interfaces.

40.   (Canceled)

41.   (Currently Amended) ~~An apparatus as recited in c~~ The apparatus of Claim 27, wherein

the one or more sequences of instructions further comprise instructions which, when

executed by the one or more processors, cause the one or more processors to perform

Ser. No. 10/718,175 filed 11/19/2003
Kajekar et al – GAU 2453 (Chea)
Reply to Final Office Action with RCE

the step of receiving third information that specifies ~~wherein the~~ packet parameters

~~specify information~~ corresponding to a plurality of different packets.

42.   (Currently Amended) ~~An apparatus as recited in c~~ The apparatus of Claim 27, wherein

the instructions that cause the one or more processors to perform the step of

representing comprise instructions which, when executed by the one or more

processors, cause the one or more processors to perform the steps of:

for a neighbor network device being represented as having been reached by the packet,

      determining if a static routing table is present; and

if the static routing table is present, then

      accessing the static routing table, and

      determining an outbound interface through which egress of the packet from the

          neighbor network device is permitted based on the static routing table.

43.   (Currently Amended) ~~An~~ The apparatus of ~~c~~Claim 42, wherein the one or more

sequences of instructions further comprise instructions which, when executed by the

one or more processors, cause the one or more processors to perform the step of not

considering any outbound interface through which egress of the packet is permitted by

the static routing table but is not permitted by an access control list associated with the

security policy data.

44.   (Currently Amended) ~~An apparatus as recited in c~~ The apparatus of Claim 27, wherein

the instructions that cause the one or more processors to perform the step of

representing comprise instructions which, when executed by the one or more

Ser. No. 10/718,175 filed 11/19/2003
Kajekar et al – GAU 2453 (Chea)
Reply to Final Office Action with RCE

processors, cause the one or more processors to perform the steps of:

for a neighbor network device for which it is determined that the packet could reach,

determining if a static routing table is present; and

if the static routing table is not present, then for each outbound interface of the neighbor

network device, representing an egress by the packet as part of the representing

of the possible travel of the packet.

45.   (Currently Amended) ~~An apparatus as recited in c~~ The apparatus of Claim 27, wherein

the ~~one or more sequences of~~ instructions that cause the one or more processors to

perform the step of receiving the first information further comprise instructions which,

when executed by the one or more processors, cause the one or more processors to

perform the step of receiving packet parameters that support transmission control

protocol flags.

46.   (Currently Amended) ~~An apparatus as recited in c~~ The apparatus of Claim 27, wherein

the ~~results~~ output comprises a graphical display of at least ~~allowed paths of the packet~~

the second information.

47.   (Currently Amended) ~~An apparatus as recited in c~~ The apparatus of Claim 27, wherein

the graphical display also includes at least a mapping of the set of network devices and

connections between the network devices in the set of network devices.

48.   (Canceled)

49.   (Currently Amended) A non-transitory computer-readable storage medium storing one

Ser. No. 10/718,175 filed 11/19/2003
Kajekar et al – GAU 2453 (Chea)
Reply to Final Office Action with RCE

or more sequences of instructions that comprise instructions which, when executed by

the one or more processors, cause the one or more processors to perform the steps of:

receiving first information that identifies a packet;

representing a possible travel of [[a]] the packet in a network based on topology data

and on security policy data;

wherein the step of representing comprises:

checking the first information against an inbound access control list (ACL),

included in the security policy data, of an interface of a network device

comprising a network entry point for the packet, wherein checking the

first information against the inbound ACL includes determining whether

the inbound ACL permits ingress of the packet at the network device;

if the inbound ACL permits the ingress of the packet at the network device,

checking the first information against one or more outbound ACLs for

each outbound interface of the network device to determine one or more

possible outbound interfaces on which egress of the packet is permitted

from the network device;

checking the topology data to determine one or more neighbor network devices

that the packet could reach, wherein the one or more neighbor network

devices are respectively connected to the one or more possible outbound

interfaces on which the egress of the packet is permitted from the

network device;

for each of the one or more possible outbound interfaces on which the egress of

the packet is permitted, repeating the checking steps with respect to for

each neighbor network device, of the one or more neighbor network

Ser. No. 10/718,175 filed 11/19/2003
Kajekar et al – GAU 2453 (Chea)
Reply to Final Office Action with RCE

devices, that is connected to each of the one or more possible outbound

interfaces;

providing an output that specifies a possible penetration of the packet into the network,

based on the step of representing, wherein the output comprises second

information that specifies one or more of: possible paths that the packet could

take in the network, and a set of network devices that the packet could reach in

the network.

50.   (Currently Amended) [[A]] The non-transitory computer-readable storage medium as

recited in of Claim 49, wherein the security policy data comprises one or more access

control lists of one or more network devices in the network.

51.   (Currently Amended) [[A]] The non-transitory computer-readable storage medium as

recited in of Claim 49, wherein the one or more sequences of instructions further

comprise instructions which, when executed by the one or more processors, cause the

one or more processors to perform the step of receiving the first information comprises

packet parameters.

52.   (Currently Amended) [[A]] The non-transitory computer-readable storage medium as

recited in of Claim 51, wherein the packet parameters comprise an identifier of the

network entry point where the packet enters the network.

53.   (Currently Amended) [[A]] The non-transitory computer-readable storage medium as

recited in of Claim 51, wherein the packet parameters comprise a destination address.

Ser. No. 10/718,175 filed 11/19/2003
Kajekar et al – GAU 2453 (Chea)
Reply to Final Office Action with RCE

54.   (Currently Amended) [[A]] The non-transitory computer-readable storage medium as recited in of Claim 51 49, wherein the one or more sequences of instructions further comprise instructions which, when executed by the one or more processors, cause the one or more processors to perform the step of reading the topology information data from a topology database.

55.   (Currently Amended) [[A]] The non-transitory computer-readable storage medium as recited in of Claim 49, wherein the topology data is based on input related to a user interface.

56.   (Currently Amended) [[A]] The non-transitory computer-readable storage medium as recited in of Claim 49, wherein the security policy data is based on access control lists associated with input related to a user interface.

57.   (Currently Amended) [[A]] The non-transitory computer-readable storage medium as recited in of Claim 49, wherein the one or more sequences of instructions that cause the one or more processors to perform the step of representing further comprise instructions which, when executed by the one or more processors, cause the one or more processors to perform the step of determining a maximum penetration point.

58.   (Currently Amended) [[A]] The non-transitory computer-readable storage medium as recited in of Claim 49, wherein the instructions that cause the one or more processors to perform the step of representing comprise instructions which, when executed by the one or more processors, cause the one or more processors to perform the step of accessing

Ser. No. 10/718,175 filed 11/19/2003
Kajekar et al – GAU 2453 (Chea)
Reply to Final Office Action with RCE

the security policy data and the topology data related to a neighbor network device for which it has been determined that the packet could reach.

59.   (Currently Amended) [[A]] The non-transitory computer-readable storage medium ~~as recited in~~ of Claim 49, wherein the instructions that cause the one or more processors to perform the step of representing comprise instructions which, when executed by the one or more processors, cause the one or more processors to perform the step of determining whether ingress is allowed to a neighbor network device ~~whose inbound interface~~ for which it has been determined that the packet could reach.

60.   (Currently Amended) [[A]] The non-transitory computer-readable storage medium ~~as recited in~~ of Claim 49, wherein the instructions that cause the one or more processors to perform the step of representing comprise instructions which, when executed by the one or more processors, cause the one or more processors to perform the step of determining whether there are any neighboring network devices to a neighbor network device for which it has been determined that the packet could reach.

61.   (Currently Amended) [[A]] The non-transitory computer-readable storage medium ~~as recited in~~ of Claim 49, wherein the instructions that cause the one or more processors to perform the step of representing comprise instructions which, when executed by the one or more processors, cause the one or more processors to perform the step of determining whether there are any possible outbound interfaces that have not yet been checked for whether there is another network device connected thereto.

Ser. No. 10/718,175 filed 11/19/2003
Kajekar et al – GAU 2453 (Chea)
Reply to Final Office Action with RCE

62.   (Currently Amended) [[A]] The non-transitory computer-readable storage medium as

recited in of Claim [[49]] 61, wherein the instructions that cause the one or more

processors to perform the step of representing comprise instructions which, when

executed by the one or more processors, cause the one or more processors to perform

the step of recursively applying the step of determining whether there are any outbound

interfaces.

63.   (Canceled)

64.   (Currently Amended) [[A]] The non-transitory computer-readable storage medium as

recited in of Claim 49, wherein the one or more sequences of instructions further

comprise instructions which, when executed by the one or more processors, cause the

one or more processors to perform the step of receiving third information that specifies

packet parameters specifying information corresponding to a plurality of different

packets.

65.   (Currently Amended) [[A]] The non-transitory computer-readable storage medium as

recited in of Claim 49, wherein the instructions that cause the one or more processors to

perform the step of representing comprise instructions which, when executed by the one

or more processors, cause the one or more processors to perform the steps of:

for a neighbor network device that could be reached by the packet, determining if a

        static routing table is present; and

if the static routing table is present, then

        accessing the static routing table, and

Ser. No. 10/718,175 filed 11/19/2003
Kajekar et al – GAU 2453 (Chea)
Reply to Final Office Action with RCE

determining an outbound interface through which egress of the packet <u>from the</u>

<u>neighbor network device</u> is permitted based on the static routing table.

66. (Currently Amended) [[A]] <u>The non-transitory</u> computer-readable storage medium of

~~c~~<u>C</u>laim 65, wherein the one or more sequences of instructions further comprise

instructions which, when executed by the one or more processors, cause the one or more

processors to perform the step of not considering any outbound interface through which

egress of the packet is permitted by the static routing table but is not permitted by an

access control list associated with the security policy data.

67. (Currently Amended) [[A]] <u>The non-transitory</u> computer-readable storage medium ~~as~~

~~recited in~~ <u>of</u> Claim ~~51~~ <u>49</u>, wherein the instructions that cause the one or more processors

to perform the step of representing comprise instructions which, when executed by the

one or more processors, cause the one or more processors to perform the steps of:

for a neighbor network device that could be reached by the packet, determining if a

      static routing table is present; and

if the static routing table is not present, then for each outbound interface of the neighbor

      network device, representing an egress by the packet as part of the representing

      of the <u>possible</u> travel of the packet.

68. (Currently Amended) [[A]] <u>The non-transitory</u> computer-readable storage medium ~~as~~

~~recited in~~ <u>of</u> Claim ~~51~~ <u>49</u>, wherein the ~~one or more sequences of~~ instructions <u>that cause</u>

<u>the one or more processors to perform the step of receiving the first information</u> further

comprise instructions which, when executed by the one or more processors, cause the

Ser. No. 10/718,175 filed 11/19/2003
Kajekar et al – GAU 2453 (Chea)
Reply to Final Office Action with RCE

one or more processors to perform the step of receiving packet parameters that support

transmission control protocol flags.

69.   (Currently Amended) [[A]] The non-transitory computer-readable storage medium as

recited in of Claim 51 49, wherein the results output comprises a graphical display of at

least allowed paths of the packet the second information.

70.   (Currently Amended) [[A]] The non-transitory computer-readable storage medium as

recited in of Claim 69 49, wherein the graphical display also includes at least a mapping

of the set of network devices and connections between the network devices in the set of

network devices.

71.   (Canceled)

72.   (Currently Amended) An apparatus for determining network penetration comprising:

means for receiving first information that identifies a packet;

means for representing a possible travel of [[a]] the packet in a network based on

topology data and on security policy data;

wherein the means for representing comprise:

means for checking the first information against an inbound access control list

(ACL), included in the security policy data, of an interface of a network

device comprising a network entry point for the packet, wherein the

means for checking the first information against the inbound ACL

include means for determining whether the inbound ACL permits ingress

Ser. No. 10/718,175 filed 11/19/2003
Kajekar et al – GAU 2453 (Chea)
Reply to Final Office Action with RCE

of the packet at the network device;

means for checking the first information against one or more outbound ACLs for

each outbound interface of the network device to determine one or more

possible outbound interfaces on which egress of the packet is permitted

from the network device when the inbound ACL permits the ingress of

the packet at the network device;

means for checking the topology data to determine one or more neighbor

network devices that the packet could reach, wherein the one or more

neighbor network devices are respectively connected to the one or more

possible outbound interfaces on which the egress of the packet is

permitted from the network device;

means for repeatedly invoking the means for checking the first information

against the inbound ACL, ~~and~~ the means for checking the first

information against the one or more outbound ACLs, and the means for

checking the topology data ~~with respect to~~ for each neighbor network

device, of the one or more neighbor network devices, that is connected to

each of the one or more possible outbound interfaces on which the egress

of the packet is permitted from the network device;

means for providing ~~an~~ penetration output that specifies a possible penetration of the

packet into the network, based on output from the means for representing,

wherein the penetration output comprises second information that specifies one

or more of: possible paths that the packet could take in the network, and a set of

network devices that the packet could reach in the network.